



NeoSapphire H510

- True high-availability solution with real-time data synchronization between 2 complete nodes
- Symmetric active-active for high availability with essentially zero downtime
- Abundant software functions for OLTP, VDI and database applications



NeoSapphire All-Flash Array



NeoSapphire H510 All-Flash Array

SPECIFICATIONS

Form Factor	2U rack mount	
IOPS for 4KB Random Writes ¹	360K sustained	
Flash Management	FlexiRemap [®] technology	
Usable Capacity ²	Max. 28TB	
Number of SSDs	24	
SSD Type	SATA	
Connectivity	8 x 10GbE SFP+	Or 4 x 16G Fibre Channel LC SFP+
Storage Protocol	iSCSI	Or Fibre Channel
Management Interface	Web GUI (via HTTP/HTTPS)	CLI (via serial port)
Power Supply	1000W/1280W 1+1 redundant	
Feature Highlight	<ul style="list-style-type: none"> • High Availability via shared-nothing architecture with symmetric Active-Active nodes • No single point of failure • Efficient FlexiDedupe[™] data reduction • Outstanding write-through performance 	
Software function	<ul style="list-style-type: none"> • Free Clone • Snapshot • Snapshot Backup/Recovery • Group Snapshot • Remote Replication • Thin Provisioning 	<ul style="list-style-type: none"> • Thick Provisioning • Inline Deduplication • Background Deduplication • vSphere Web Client Plug-in • SED • RESTful API
Certification ⁴	<ul style="list-style-type: none"> • VMware Ready • VMware VAAI Block • Microsoft Windows Server 2016 • Microsoft Windows Server 2012 R2 	<ul style="list-style-type: none"> • Microsoft Windows Server 2012 • DataCore SMPA Qualified • Tiger Technology Certified
Dimensions (W x D x H)	438mm x 730mm x 88mm (17.3in x 28.8in x 3.5in)	
Net Weight ³	24.8kg (54.7lb)	
Environmental Temperature	Operating: 10°C to 35°C (50°F to 95°F) Storage (non-operating): -20°C to 60°C (-4°F to 140°F)	
Environmental Humidity	Operating: 10% to 90% non-condensing Storage (non-operating): 5% to 95% non-condensing	

¹ Based on designated testing conditions. IOPS performance is tested on one standalone H510. Performance may vary with different applications or product configurations.

² Usable capacity refers to the approximation of the storage capacity that users can have. The accurate usable capacity may vary depending on software configurations and other factors.

³ Weight may vary depending on components and manufacturing variability.

⁴ The certification of H510 will be available in Q1, 2018.

©2015-2018. All rights reserved. AccelStor, FlexiRemap, and NeoSapphire are trademarks or registered trademarks of AccelStor Ltd. in the United States of America and/or other countries. Other names and brands may be claimed as the property of others. Pictures are not contractual. In a continuing effort to improve the quality of our products, information in this brochure is subject to change without notice. Images appearing are only representations of some of the configurations available. Availability may vary depending on region. AccelStor Ltd. reserves the right to the interpretation of the above specifications, terms and conditions.